

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ARALDITE® STANDARD ULTRA RESIN

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy constituents

#### 1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA  
Address : Everslaan 45  
3078 Everberg  
Belgium  
Telephone : +41 61 299 20 41  
Telefax : +41 61 299 20 40  
E-mail address of person responsible for the SDS : Global\_Product\_EHS\_AdMat@huntsman.com

#### 1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234  
France ORFILA: +33(0)145425959  
ASIA: +65 6336-6011  
China: +86 20 39377888  
+86 532 83889090  
India: + 91 22 42 87 5333  
Australia: 1800 786 152  
New Zealand: 0800 767 437  
USA: +1/800/424.9300

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2      H315: Causes skin irritation.  
Eye irritation, Category 2      H319: Causes serious eye irritation.  
Skin sensitisation, Category 1      H317: May cause an allergic skin reaction.  
Long-term (chronic) aquatic hazard, Category 2      H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

**ARALDITE® STANDARD ULTRA RESIN**

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P261 Avoid breathing mist or vapours.  
P264 Wash skin thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P391 Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

Bisphenol A - epoxy resins, number average MW >700 - <1100

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No.	Classification	Concent
---------------	---------	----------------	---------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

	EC-No. Index-No. Registration number		ration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411  specific concentration limit Skin Irrit. 2; H315 >= 5 % Eye Irrit. 2; H319 >= 5 %	>= 70 - < 90
Reaction mass of 2,2'-[methylenebis(2, ,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4, ,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2,ylmethoxy)benzyl]phenoxy}methyl)oxirane,	- - 01-2119454392-40	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 2.5 - < 10
Bisphenol A - epoxy resins, number average MW >700 - <1100	25068-38-6 Polymer	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 10

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Treat symptomatically.  
Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
  
Carbon oxides  
Halogenated compounds

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Refer to protective measures listed in sections 7 and 8.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	25.01.2021	400001021217	17.07.2019
			Date of first issue: 20.07.2018

Print Date 17.06.2022

Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

### 7.3 Specific end use(s)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

Specific use(s) : No data available

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Silica, amorphous, fumed, cryst.-free	112945-52-5	TWA (inhalable dust)	6 mg/m <sup>3</sup> (Silica)	GB EH40
		TWA (Respirable dust)	2.4 mg/m <sup>3</sup> (Silica)	GB EH40

##### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4.93 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	0.75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.87 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	0.0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.5 mg/kg bw/day
Bis(2-ethylhexyl) adipate	Workers	Inhalation	Long-term systemic effects	17.8 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	25.5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4.4 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	13 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1.7 mg/kg bw/day
Silica, amorphous, fumed, cryst.-free	Workers	Inhalation	Long-term systemic effects	4 mg/m <sup>3</sup>

##### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0.006 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

ne		
Remarks:	Assessment Factors	
	Marine water	0.001 mg/l
	Assessment Factors	
	Fresh water sediment	0.341 mg/kg dry weight (d.w.)
	Equilibrium method	
	Marine sediment	0.034 mg/kg dry weight (d.w.)
	Equilibrium method	
	Soil	0.065 mg/kg dry weight (d.w.)
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg
Bis(2-ethylhexyl) adipate	Soil	0.865 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

#### Hand protection

Material : butyl-rubber  
Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber  
Break through time : 10 - 480 min

Material : Neoprene gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : light cream

Odour : slight

Odour Threshold : No data is available on the product itself.

pH : 6  
Concentration: 500 g/l

Melting point/freezing point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : 210 °C  
Method: Pensky-Martens closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Burning rate : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : 0.0001 kPa

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : 1.15 g/cm<sup>3</sup> (25 °C)

Solubility(ies)

Water solubility : No data is available on the product itself.

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

Viscosity : No data is available on the product itself.

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

### 9.2 Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : None known.

### 10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases  
Strong oxidizing agents

### 10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide  
carbon monoxide  
Halogenated compounds

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: No mortality observed at this dose.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:  
Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : No data available

### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:  
Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

### **Skin corrosion/irritation**

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit  
Exposure time: 4 h  
Assessment: Irritating to skin.  
Method: OECD Test Guideline 404

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Result: Irritating to skin.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Method: OECD Test Guideline 404

Result: Skin irritation

### Serious eye damage/eye irritation

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Irritating to eyes.

Method: OECD Test Guideline 405

Result: Irritating to eyes.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Eye irritation

### Respiratory or skin sensitisation

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin

Species: Mouse

Method: OECD Test Guideline 429

Result: The product is a skin sensitiser, sub-category 1B.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:

Exposure routes: Skin

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Exposure routes: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

Assessment: No data available

### Germ cell mutagenicity

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Result: positive

: Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)

Result: negative

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

: Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive

: Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: Positive results were obtained in some in vitro tests.

: Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Test Type: in vivo assay  
Test species: Mouse (male)  
Cell type: Germ  
Application Route: Oral  
Dose: 3333, 10000 mg/kg  
Result: negative

Test Type: gene mutation test  
Test species: Rat (male)  
Cell type: Somatic  
Application Route: Oral  
Dose: 50,250,500,1000 mg/kg bw/day  
Method: OECD Test Guideline 488  
Result: negative

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:  
Genotoxicity in vivo : Cell type: Somatic  
Application Route: Oral  
Exposure time: 48 h  
Dose: 2000 mg/kg  
Method: OECD Test Guideline 474  
Result: negative

Cell type: Somatic  
Application Route: Oral  
Dose: 2000 mg/kg  
Method: OECD Test Guideline 486  
Result: negative

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vivo : Cell type: Germ  
Application Route: Oral  
Method: OECD Test Guideline 478  
Result: negative

Cell type: Somatic  
Application Route: Oral  
Dose: 0 - 5000 mg/kg  
Method: OPPTS 870.5395  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

Germ cell mutagenicity- Assessment : No data available

### Carcinogenicity

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male

Application Route: Oral

Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment: 7 days/week

No observed adverse effect level: 15 mg/kg bw/day

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Mouse, male

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0, 0.1, 10, 100 mg/kg bw/day

Frequency of Treatment: 3 days/week

No-observed-effect level: 0.1 mg/kg body weight

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Rat, female

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0.1, 100, 1000 mg/kg bw/day

Frequency of Treatment: 5 days/week

No-observed-effect level: 100 mg/kg body weight

Method: OECD Test Guideline 453

Result: negative

Species: Rat, female

Application Route: Oral

Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment: 7 days/week

No observed adverse effect level: 100 mg/kg bw/day

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Rat, females

Application Route: Oral

Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment: 7 days/week

No-observed-effect level: 2 mg/kg bw/day

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rat, male and female

Application Route: Oral

Exposure time: 24 month(s)

Dose: 15 mg/kg

Frequency of Treatment: 7 daily

Method: OECD Test Guideline 453

Result: negative

Carcinogenicity - Assessment : No data available

### Reproductive toxicity

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility

: Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 milligram per kilogram

Duration of Single Treatment: 238 d

Frequency of Treatment: 1 daily

General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight

General Toxicity F1: No-observed-effect level: 750 mg/kg body weight

Symptoms: No adverse effects

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic development were detected.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic development were detected.

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rat, male and female

Application Route: Oral

General Toxicity - Parent: No-observed-effect level: 750 mg/kg body weight

General Toxicity F1: No-observed-effect level: 750 mg/kg body weight

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic development were detected.

#### Components:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development : Species: Rabbit, female  
Application Route: Dermal  
Dose: 0, 30, 100 or 300 milligram per kilogram  
Duration of Single Treatment: 28 d  
Frequency of Treatment: 1 daily  
General Toxicity Maternal: No observed adverse effect level:  
30 mg/kg body weight  
Developmental Toxicity: No observed adverse effect level:  
300 mg/kg body weight  
Method: Other guidelines  
Result: No teratogenic effects

Test Type: Pre-natal  
Species: Rabbit, female  
Application Route: Oral  
Dose: 0, 20, 60 or 180 milligram per kilogram  
Duration of Single Treatment: 13 d  
Frequency of Treatment: 1 daily  
General Toxicity Maternal: No observed adverse effect level:  
60 mg/kg body weight  
Developmental Toxicity: No observed adverse effect level:  
180 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Test Type: Pre-natal  
Species: Rat, female  
Application Route: Oral  
Dose: 0, 60, 180 and 540 milligram per kilogram  
Duration of Single Treatment: 10 d  
Frequency of Treatment: 1 daily  
General Toxicity Maternal: No observed adverse effect level:  
180 mg/kg body weight  
Developmental Toxicity: No observed adverse effect level: >  
540 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:

Species: Rabbit, female  
Application Route: Dermal  
General Toxicity Maternal: No observed adverse effect level:  
30 mg/kg body weight  
Result: No teratogenic effects

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rabbit, female  
Application Route: Dermal  
General Toxicity Maternal: No observed adverse effect level:  
30 mg/kg body weight  
Method: Other guidelines



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Result: No teratogenic effects

Species: Rabbit, female  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level:  
60 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Species: Rat, female  
Application Route: Oral  
General Toxicity Maternal: No observed adverse effect level:  
180 mg/kg body weight  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Repeated dose toxicity

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: oral (gavage)

Exposure time: 14 Weeks Number of exposures: 7 d

Dose: 0, 50, 250, 1000 mg/kg/day

Method: OECD Test Guideline 408

Species: Rat, male and female

NOAEL: >= 10 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks Number of exposures: 5 d

Dose: 0, 10, 100, 1000 mg/kg/day

Method: OECD Test Guideline 411

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks Number of exposures: 3 d

Dose: 0, 1, 10, 100 mg/kg/day

Method: OECD Test Guideline 411

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

:  
Species: Rat, male and female  
NOAEL: 250 mg/kg  
Application Route: Ingestion  
Exposure time: 13 Weeks Number of exposures: 7 d  
Method: Subchronic toxicity

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rat, male and female  
NOAEL: 50 mg/kg  
Application Route: Ingestion  
Exposure time: 14 Weeks Number of exposures: 7 d  
Method: Subchronic toxicity

Species: Rat, male and female  
NOEL: 10 mg/kg  
Application Route: Skin contact  
Exposure time: 13 Weeks Number of exposures: 5 d  
Method: Subchronic toxicity

Repeated dose toxicity - Assessment : No data available

### Aspiration toxicity

No data available

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	25.01.2021	400001021217	17.07.2019
			Date of first issue: 20.07.2018

Print Date 17.06.2022

### Toxicology, Metabolism, Distribution

No data available

### Neurological effects

No data available

### Further information

Ingestion: No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 : 11 mg/l  
plants : Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: EPA-660/3-75-009

NOEC : 4.2 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l  
Exposure time: 3 h  
Test Type: static test  
Test substance: Fresh water

Toxicity to daphnia and other : NOEC: 0.3 mg/l  
aquatic invertebrates : Exposure time: 21 d  
(Chronic toxicity) : Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Test substance: Fresh water

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

Method: OECD Test Guideline 211

### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:

- Toxicity to fish : LC50 (Fish): 2.54 mg/l  
Exposure time: 96 h  
Method: Calculation method
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.55 mg/l  
Exposure time: 48 h  
Method: Calculation method
- Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 1.8 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 201
- Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l  
Exposure time: 3 h  
Test Type: static test  
Test substance: Fresh water
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.3 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Test substance: Fresh water  
Method: OECD Test Guideline 211  
Remarks: Information given is based on data obtained from similar substances.
- Bisphenol A - epoxy resins, number average MW >700 - <1100:
- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: Fresh water  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EgC50 (Selenastrum capricornutum (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

### 12.2 Persistence and degradability

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge, non-adapted  
Concentration: 20 mg/l  
Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)  
pH: 4  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)  
pH: 9  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)  
pH: 7  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:

Biodegradability : Inoculum: activated sludge  
Concentration: 3 mg/l  
Result: Not biodegradable  
Biodegradation: ca. 0 %  
Exposure time: 28 d  
Method: Directive 67/548/EEC Annex V, C.4.E.

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Biodegradability : Test Type: aerobic  
Inoculum: Sewage (STP effluent)  
Concentration: 20 mg/l  
Result: Not biodegradable  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)  
pH: 4  
Method: OECD Test Guideline 111  
Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)  
pH: 9  
Method: OECD Test Guideline 111

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)

pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

### 12.3 Bioaccumulative potential

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31  
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3.242 (25 °C)  
pH: 7.1  
Method: OECD Test Guideline 117

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:  
Bioaccumulation : Species: Fish  
Bioconcentration factor (BCF): 150  
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 2.7 - 3.6  
Method: OECD Test Guideline 117

Bisphenol A - epoxy resins, number average MW >700 - <1100:  
Bioaccumulation : Species: Fish  
Bioconcentration factor (BCF): 31  
Remarks: Does not bioaccumulate.

### 12.4 Mobility in soil

#### Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among environmental compartments : Koc: 445

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:  
Distribution among environmental compartments : Koc: 4460  
Method: OECD Test Guideline 121

Bisphenol A - epoxy resins, number average MW >700 - <1100:  
Distribution among environmental compartments : Koc: 445

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
Dispose of as hazardous waste in compliance with local and national regulations.  
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

## SECTION 14: Transport information

#### IATA

14.1 UN number or ID number : UN 3082

14.2 UN proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo) : 964

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

aircraft)  
Packing instruction : 964  
(passenger aircraft)

### IATA (Passenger)

Environmentally hazardous : yes

### IATA (Cargo)

Environmentally hazardous : yes

### IMDG

14.1 UN number or ID number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

EmS Code : F-A, S-F

### 14.5 Environmental hazards

Marine pollutant : yes

### ADR

14.1 UN number or ID number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

### 14.5 Environmental hazards

Environmentally hazardous : yes

### RID

14.1 UN number or ID number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

### 14.5 Environmental hazards

Environmentally hazardous : yes

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version 1.2      Revision Date: 25.01.2021      SDS Number: 400001021217      Date of last issue: 17.07.2019  
Date of first issue: 20.07.2018

Print Date 17.06.2022

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

#### Inventories

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

### 15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

## SECTION 16: Other information

### Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)

### Further information

#### Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

#### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**HUNTSMAN**

Enriching lives through innovation

## ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.